



COMPACT BY NABOO

Model **061**



Capacity	n - inch	6 - 12 x 20"
Distance between layers	inch	2.36
Number of meals		30 / 80
External dimensions	inch	20.08 x 31.50 x 34.65" h
Packing dimensions	inch	22.44 x 36.61 x 40.16" h

		Direct steam
Electric models		COEN061
Total electric power	KW	7.75
Consumption	Amps	21.51
Power supply voltage	V - 60 Hz	3Ph / 208

STANDARD EQUIPMENT

- AUTOMATIC CLEANING SYSTEM LCS - SUPPLIED WITH 1 LIQUID CLEANSER CARTRIDGE CDL05, 11 LBS.
- MULTIPOINT CORE PROBE Ø 0.12".
- WI-FI CONNECTION
- USB CONNECTION

OPTIONAL - TO BE REQUESTED WHEN ORDERING OVEN

- NPS - OPPOSITE HINGED DOOR
- APDS - DOUBLE RELEASE DOOR OPENING
- SN - EXTRA CHARGE FOR ENERGY SAVING SYSTEM CONNECTION - ELECTRIC MODELS ONLY
- CETH - EXTRA CHARGE FOR ETHERNET CONNECTION
- MKC061 - MARINE VERSION KIT. FLANGED FEET - DOOR IMMOBILIZING LOCK - SPECIAL RACK RAILS - FULL AISI 304 - ELECTRIC MODELS ONLY

EXTRA ACCESSORIES THAT CAN BE INSTALLED FOLLOWING PURCHASE

- KSA001 - NEEDLE CORE PROBE Ø 0.04".
- KSM002 - MULTIPROBES SYSTEM, 2 MULTIPOINT CORE PROBES. Ø 0.12"
- ICLD - HAND SHOWER WITH FITTINGS AND CONNECTIONS
- ICFX01 - FAT FILTER
- PAC061 - STAINLESS STEEL HEAT SHIELD FOR THE UNIT SIDE PANEL

By requesting at the order the electric version is also available in single phase